

**The “Rocky” Series Hard Hats
(HP141R / HP142R)**



HP141R – CSA Type 1
Class E
HP142R – CSA Type 2
Class E

PRODUCT DESCRIPTION:

The “ROCKY” series of hard hats have been conceived primarily for people working at heights or in confined spaces as well as for rescue teams, tree trimmers, win turbine assembly and telecommunication tower climbers will find the Rocky ideal to wear. It is also ideal for sportsman for rock climbing. Made of a Polycarbonate mix with ABS making the hat ultra light while offering an exceptional protection against chocks and impacts. CSA class E non-vented hat offering maximum protection against electrical shock. Available in Type 1 and Type 2. The absence of the front peak offers a total non-obstructed vision. The universal slot on each side of the helmet allows you the opportunity to install either Ear Muffs or a lamp bracket on the Hat. The 4-point suspension with the exclusive “Sure Lock II” ratchet adjustment offers the perfect fit for all types of heads small or large. The shell offers a large printing surface in front, in the back even on the sides so that you can apply your Logo or all other type of printing. The Rocky comes with an integrated high quality 4-point chin-strap easily adjustable.

Product Number	Description	EA Weight	Inner Packs	Case Quantity	Case Dimensions	Case Weight
HP141R	“Sure-Lock II” Ratchet suspension & Permanently attached 4 point Chin-Strap, CSA Type 1 Class E	0.43 kg. 0.95 lbs	1 EA	8 EA	53.3 x 47 x 33 cm 21” x 18.5” x 13”	5.1 kg 11.4 lbs
HP142R	“Sure-Lock II” Ratchet suspension & Permanently attached 4 point Chin -Strap, CSA Type 2 Class E	0.45 kg. 1.00 lbs	1 EA	8 EA	53.3 x 47 x 33 cm 21” x 18.5” x 13”	5.44 kg 12.1 lbs

The “Rocky” Series Hard Hats (HP141R / HP142R)

PRODUCT CERTIFICATION:

HP141R: certified to the **CSA Z94.1 – 15** (Canada) standard as **Type 1, Class E** and meets **ANSI Z89.1 – 2014** (USA) standard as **Type I, Class E**

HP142R: certified to the **CSA Z94.1 – 05** (Canada) standard as **Type 2, Class E** And meets **ANSI Z89.1 – 2003** (USA) standard as **Type II, Class E.**

PRODUCT CHARACTERISTICS:

HP141R & HP142R:

Shell Material:	Polycarbonate/ABS
Heat Resistance:	375°F (190°C)
Suspension:	4 points of attachment
Suspension Tabs:	HDPE
Suspension Assembly:	HDPE
Suspension Straps:	
Material:	Woven Nylon Webbing
Width:	23/32”
Breaking Strength:	300 pounds minimum
Elongation:	19%
Inside Foam Crown (Type 2 only):	Polystyrene
Crown Pad Material:	Urethane Foam laminated with Vinyl on one side
Sweatband Material:	Urethane Foam laminated with Vinyl on one side
Sure-Lock II Ratchet Mechanism:	Acetal
Chin Strap Material:	Polypropylene
Weight: HP141R:	430 gram / 0.95 lbs
HP142R:	455 gram / 1.00 lbs

COUNTRY OF ORIGIN:

Made in Canada

MATERIAL DECLARATION:

We declare that the materials and processes used in the manufacturing of this product are not known to cause harmful effects to the wearer. However, it is the users’ responsibility to do the proper tests for the specific application.

DISCLAIMER:

The data, included in this document, incorporates the best information currently available to DSI Safety Inc. and it is derived from sources believed to be reliable. DSI Safety Inc. makes no warranties to the accuracy of the source material.