# MAGIC WRENCH \* AEROSOL

#### **DESCRIPTION**

MAGIC WRENCH® Super Penetrant attacks rust and Appearance corrosion quickly and safely to free corroded parts, loosen nuts and aid in the disassembly of mechanical components. Fluid Type Versatile synthetic formula penetrates, lubricates, removes Propellant moisture and protects chains, cables, slides and other ISO Viscosity Grade moving parts. Silicone free. Nonevaporative. Safe on all SAE Viscosity Grade metals and plastics. Excellent for both food grade and Density (lb/gal) non-food grade applications. Low V.O.C. (Volatile Organic Specific Gravity Components) formula assures not only an environmen- Flash Point (ASTM D-92) tally responsible product, but more active ingredients to Copper Strip Corrosion enhance product performance.

- NSF H-1 Registered #048230
- Penetrates Fast
- Synthetic Fluids
- Biodegradable
- Destroys Rust
- Lubricates
- Safe on Metal & Plastic
- Convenient aerosol package
- Low VOC Formula
- Silicone Free
- Ozone Safe
- Nonevaporative

### **APPLICATIONS**

**MAGIC WRENCH** is a premium, synthetic product that may be used as a light machine oil, penetrating oil or rust preventive. Excellent for use on equipment such as chains, linkages, cams and slids, stirrups on bottle-filling machines, valves, pins, hinges, cables, etc. In addition, MAGIC **WRENCH** is an ideal product for the lubrication and conditioning of air tools.

NSF H-1 Registered (Reg. No. 048230). Conforms to FDA Regulation CFR 21, Section 178,3570 for incidental Food Contact.

#### PRODUCT CHARACTERISTICS

Clear, pale yellow fluid w/ faint odor Ester, PAO & White Oils Hydrocarbon 32 10 6.92 0.83 >450°F (232°C)

(ASTM D-130)

Pour Point (ASTM D-97) 10°F (-12°C) Spray Pattern (from 12" distance) 1" cone

-60°F (-51°C) to Service Rating

350°F (177°C)

NFPA 30B Storage Class Level II **VOC Content** 10g/Liter

(Without Propellant)

6" - 8" Flame Extension Test

#### **PACKAGING**

Code No. **Container Size** Container 39541 13 oz. Aerosol

#### LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential dam-

## CORPORATE LOCATIONS

Houston, Texas-World Headquarters

0813

Maidenhead, England

Edmonton, Canada

JET-LUBE, INC. 4849 HOMESTEAD RD., P.O. BOX 21258 (77226-1258) **HOUSTON, TX 77028** 

WATS: 800-538-5823 PHONE: 713-674-7617 FAX: 713-678-4604 E-MAIL: sales@jetlube.com

www.jetlube.com